Page 1 SLE-3009-A

Date: March 3, 1989

Supersedes Revision Dated: 11-25-87

## MATERIAL SAFETY DATA SHEET

Fiber-Resin Corporation 170 W. Providencia Avenue Burbank, CA 91503) Date: March 3, 1989
Prepared by: Sam Engel
Telephone:1-800-624-9487

### PRODUCT IDENTIFICATION

Fiber-Resin Name: SLE-3009-A

Product Class: Epoxy Resin System

DOT Proper Shipping Name: Non-hazardous

WARNING STATEMENT

Potential dermal sensitizer

### PRECAUTIONARY MEASURES

Avoid skin contact with product at all times.

### EMERGENCY AND FIRST AID PROCEDURES

If in eye: Flush immediately with water for 15 minutes. Consult

a physician if irritation persists.

If on skin: Wash affected area with soap and water. Launder

contaminated clothing before reuse.

In case of fire: Extinguish with water spray, foam, dry chemical

or carbon dioxide.

Spill or leak: Wear rubber gloves and wipe up with absorbent

material. Residue may be removed with chlorinated

solvent.

### HAZARDOUS INGREDIENTS

ACGIH TLV
Material Name/CAS# In Product OSHA PEL (1988,1989)

Bisphenol A Diglycidyl Ether >70% NE NE

Resin (25048-38-4)

WE = Not Established NA = Not Applicable Page 2 SLE-3009-A

This MSDS is prepared to comply with the OSHA Hazard Communication Standard (29 CFR 1910.1200). Unlisted ingredients are not "Hazardous" per this OSHA Standard and are considered to be trade secrets of the Fiber-Resin Corporation. Identities of trade secret ingredients (which are on the TOSCA inventory) will be made available following the procedures specified in the inventory.

#### OCCUPATIONAL CONTROL PROCEDURES

Eye Protection:

Safety Glasses

Skin Protection:

Prevent contact by using rubber gloves and appropriate protective clothing. Launder contaminated clothing before reuse.

Respiratory Protection: Not normally required

Ventilation:

Standard industrial ventilation.

## FIRE PROTECTION

Flash Point/Method:

490 F, Tag closed cup

Extinguishing Media:

Use water spray, foam, dry chemical or

carbon dioxide.

Special Fire Fighting

Frocedures:

Use self-contained breathing apparatus and

full protective equipment.

Unusual Fire and

Explosion Hazards:

None known.

## REACTIVITY DATA

Stability:

Stable

Incompatibility:

Avoid contact with strong oxidizing agents.

Products:

Hazardous Decomposition Incomplete combustion can yield low molecular weight hydrocarbons, as well as carbon monox-

ide and carbon dioxide.

Hazardous Polymerization: Will not occur

### EFFECTS OF OVER EXPOSURE

Eyes:

Direct eye contact with the product may

cause irritation.

Skin:

Solvents are potential dermal sensitizers.

Page 3 JLE-3009-A

Inhalation:

Inhalation is not a normal route of exposure.

Chronic:

No anticipated chronic effects. This product does not contain regulated levels of NTP,

IARC, or OSHA listed carcinogens.

Existing Health Conditions Affected by Exposure:

No known effects on other illnesses.

### PHYSICAL DATA

Physical State: Weight per gallon:

Odor: Viscosity: % Solids: pH:

Green paste 11.0 pounds Sweet, aromatic

Paste >99% NA

### SPILL, LEAK & DISPOSAL INFORMATION

Spill or Leak Wear rubber gloves and wipe with absorbent material. Procedures: Residue may be removed with a chlorinated solvent.

Waste Disposal: This product does not meet the definition of hazardous waste under the U.S. EFA Hazardous Waste Requlations 40 CFR 261. State or local hazardous waste regulations may apply if they are different from the federal regulation. Incinerate or dispose of in an approved industrial landfill. For additional waste disposal assistance contact the Fiber-Resin Corporation.

### STORAGE

Store in a cool dry location.

### REGULATORY INFORMATION

# TOSCA

All components of this product are registered under the regulations of the Toxic Substance Control Act.

Page 4 SLE-3009-A.

SARA TITLE III

Section 313: This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372:

Chemical Name:

CAS#

Percentage

None

This information must be included in all MSDS that are copied and distributed for this material.